

225HP OUTBOARD COMPARISON



	225 SeaPro	225 Pro XS	225 FourStroke
HP / kW	225 / 168	225 / 168	225 / 168
MidSection	Conventional MidSection (CMS)	Conventional MidSection (CMS)	Conventional MidSection (CMS)
Engine type	V-8	V-8	V-6
Displacement (CID/CC)	279 CID	279 CID	209 CID
Displacement (L)	4.6L	4.6L	3.4L
Cylinder Configuration	V-8 [64 degree] with Dual Overhead Cam (DOHC) and 32-valves	V-8 [64 degree] with Dual Overhead Cam (DOHC) and 32-valves	V-6 [64 degree] with Dual Overhead Cam (DOHC) and 24-valves
Full throttle RPM	4800-5600	5600-6200	5200-6000
Air induction	Performance-Tuned Long-Runner Intake Manifold	Performance-Tuned Long-Runner Intake Manifold	Performance-Tuned Long-Runner Intake Manifold
Fuel induction system	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization	Electronic Fuel Injection (EFI) Computer Controlled with Advanced Range Optimization
Alternator amp / Watt	85-amp (1071 Watt) with Idle Charge	85-amp (1071 Watt) with Idle Charge	85-amp (1071 Watt) with Idle Charge
Recommended fuel	Unleaded 91 RON	Unleaded 91 RON	Unleaded 91 RON
Recommended oil	NMMA Certified FCW SAE 25W-40 (Optional 10W-30 for Cold Conditions)	NMMA Certified FCW SAE 10W-30	NMMA Certified FCW SAE 10W-30
Engine protection operator warning system	SmartCraft Engine Guardian	SmartCraft Engine Guardian	SmartCraft Engine Guardian
Compatible with SmartCraft digital technology	Yes	Yes	Yes
Starting	Electric Start with SmartStart Protection	Electric Start with SmartStart Protection	Electric Start with SmartStart Protection
Controls	Remote Mechanical or Digital Throttle & Shift (DTS)	Remote Mechanical or Digital Throttle & Shift (DTS)	Remote Mechanical or Digital Throttle & Shift (DTS)
Steering	Hydraulic (standard) Power (optional) Big Tiller (optional)	Hydraulic (standard) Power (optional) Big Tiller (optional)	Hydraulic (standard) Power (optional) Big Tiller (optional)
Shaft length	"20" / 508 mm 25" / 635 mm 30" / 762 mm"	"20" / 508 mm 25" / 635 mm"	"20" / 508 mm 25" / 635 mm 30" / 762 mm"
Gearcase ratio	1.75:1	1.75:1	1.85:1
Dry weight <i>* Lightest model available</i>	527 lbs / 239 kgs	505 lbs / 229 kgs	475 lbs / 216 kgs
CARB star rating	3	3	3
Bore and stroke	3.6 in x 3.4 in / 92 mm x 86 mm	3.6 in x 3.4 in / 92 mm x 86 mm	3.6 in x 3.4 in / 92 mm x 86 mm
Ignition	SmartCraft PCM 112 Digital Inductive	SmartCraft PCM 112 Digital Inductive	SmartCraft PCM 112 Digital Inductive
Cooling system	Water-cooled with thermostat	Water-cooled with thermostat	Water-cooled with thermostat
Gear shift	F-N-R	F-N-R	F-N-R
Gearcase options	5.44"	"20": TorqueMaster 25": 5.44"	4.8"
Trim system	Power trim and tilt	Power trim and tilt	Power trim and tilt
Exhaust system	Through prop	Through prop	Through prop
Counter Rotation	Available	N/A	Available
Color	Phantom Black	Phantom Black	Phantom Black Pearl Fusion White Cold Fusion White Warm Fusion White
Lubrication system	Integrated wet sump	Integrated wet sump	Integrated wet sump
Oil Capacity	7.0 Quarts / 6.6 Liters	7.0 Quarts / 6.6 Liters	7.0 Quarts / 6.6 Liters
Maximum Trim Range	20° [-6° to 14°]	20° [-6° to 14°]	20° [-6° to 14°]
Maximum Tilt Range	73° [-6° to 67°]	73° [-6° to 67°]	73° [-6° to 67°]