



SPECIFICATIONS

Mercury® MerCruiser® 6.2L Jet Ready Inboard



HP / kW	<ul style="list-style-type: none"> • 370 / 276
Maximum RPM (WOT)	<ul style="list-style-type: none"> • 4000-5400 (Jet pump applications will limit max RPM based on jet pump and impeller capabilities)
Engine type	<ul style="list-style-type: none"> • V8, 2-valve/cylinder pushrod
Displacement (L)	<ul style="list-style-type: none"> • 6.2L
Bore and stroke	<ul style="list-style-type: none"> • 4.0 x 3.75" / 101.6 x 95.25 mm
Fuel requirement	<ul style="list-style-type: none"> • 90 RON 10% Ethanol Maximum
Engine control system	<ul style="list-style-type: none"> • SmartCraft PCM 112 Digital Inductive
Starting	<ul style="list-style-type: none"> • Electric • Smart Start Electric
Air induction	<ul style="list-style-type: none"> • Performance-Tuned Long-Runner Intake Manifold
Ignition	<ul style="list-style-type: none"> • SmartCraft PCM 112 Digital Inductive
Alternator amp / Watt	<ul style="list-style-type: none"> • Fully regulated belt-driven 70 amp (882 watt)
Water drain system	<ul style="list-style-type: none"> • Air actuated + four-plug manual drain "Season Extender"
Exhaust system	<ul style="list-style-type: none"> • Through transom
Cooling system	<ul style="list-style-type: none"> • Fresh water cooled (closed cooling)
Lubrication system	<ul style="list-style-type: none"> • Integrated wet sump
Recommended oil	<ul style="list-style-type: none"> • NMMA Certified FCW 25W-40 Synthetic Blend
Engine guardian system	<ul style="list-style-type: none"> • SmartCraft Engine Guardian
Dimensions (L x W x H)	<ul style="list-style-type: none"> • 43.5" x 30" x 30" / 1104.9 x 762 x 762 mm
Weight (engine only)	<ul style="list-style-type: none"> • 935 lbs / 424 kg

© 2023 Mercury Marine. All Rights Reserved.

Reproduction in whole or in part without permission is prohibited. Mercury Marine is a division of .